JUST RELEASED



FLYPRO® ALUMINIUM & UNISCREEN-SS

Introducing the new and improved FLYPRO® ALUMINIUM and UNISCREEN-SS flyscreens, now even better with a stronger screen fabric and a durable powder coat finish.

ALUMINIUM

NEW AND IMPROVED

HIGH

QUALITY

HIGH

CONSISTENCY

FLYPRO® **ALUMINIUM** flyscreen has been optimised to achieve a balance between ease of installation and surface flatness.

A highly consistent, deep-black powder coating creates a crisp and open appearance, as well as greater weather resistance.

FEATURES:

- Can be installed with less force
- Uniformly straight weave, compared with similar mesh fabric, makes the screen very easy and quick to install
- Improved elongation compared to similar aluminium products for better break-resistance

Strand

0.26mm

Open Area

68%

Retractable

GSM

180

Patio

APPLICATIONS:

Residential windows and doors.

Weave

18x16

Door

SPECIFICATIONS:

Material

AL5154

Window

•••		•••	•	000		•••	
Protection	Airflov					Bal Rating BAL29	
Width	L	ength	Pallet Q	ty		Code	
610mm	31	0m	64		7	115094	
760mm	31	0m	64		7	115095	
810mm	31	0m	64		7	115106	
910mm	31	0m	64		7	115107	
1220mm	31	0m	64		7	115108	
1520mm	31	0m	64		7	115109	
1830mm	31	0m	64		7	115110	
910mm	2.	.1m	64		7	115114	
1220mm	2	1m	64		7	115358	

UNISCREEN-SS

NEW AND IMPROVED

FLYPRO® **UNISCREEN-SS** has been developed as a universal flyscreen solution meeting all requirements: ease of installation, durability, invisibility, strength and corrosion resistance.

The ultra-thin strand delivers a clearer and more open visual experience, with an invisible effect.

FEATURES:

- Easy to install: No pre-creasing or tearing
- Ultra high tensile strength is more resistant to dents than standard stainless steel or aluminium products
- · Holds firm tension in the frame
- · Premium coating with deep blackness

BEST VALUE FOR BAL40

APPLICATIONS:

Bushfire prone areas. Not recommended for C4 or C5 Corrosive Zones*.

SPECIFICATIONS:

Material	Weav	е	Strand	Open Area		GSM	
SS304H	20x1	20x18 0.1		1mm 83%		120	
Window		Door		Retractable		Patio	
•••		•••		•••		•••	
Protection	Airflow	Visibili	ty Stren		Safa	Bal Rating	
OOO	Alliow	• • •				BAL40	
Width	Leng	Length		Pallet Qty		Code	
610mm	30m	30m		81		7115061	
760mm	30m	30m		81		7115062	
910mm	30m	30m		81		7115063	
1220mm	30m	30m		81		7115064	
1520mm	30m	30m		81		7115356	
1830mm	30m	30m		81		7115357	

National Customer Support Centre

Ph: 1300 551 919

Email: orders@lincolnsentry.com.au

Get Social

@@lincolnsentry

f @lincolnsentry

in Lincoln Sentry Pty. Ltd





^{*}See AS4312:2019 Atmospheric Corrosive Zones in Australia for more information.