



HEXFIX[®] Mirror Tape 2400

HEXFIX[®] Mirror Tape 2400 is a cross-linked, flexible polyethylene, double sided, closed cell foam tape. Coated with a synthetic rubber pressure sensitive adhesive, the foam tape can easily be applied to most common substrates without any mechanical fixings.

Ideally suited for automotive and construction applications including sealing, gasketing, mounting of nameplates and mirrors (must be used in conjunction with a recommended liquid adhesive for mirror installations).

Features:

- Low water absorption
- Good chemical and UV resistance
- Low irritant and odour
- Will not support mould or bacterial growth

Size	Colour	Code
24mm x 3.0mm x 23m	White	4-933-024
24mm x 1.5mm x 33m	White	4-931-524

CONTACT US

lincolnsentry.com.au
1300 551 919

GET SOCIAL

@lincolnsentry
Lincoln Sentry



Mirror Tape 2400

Product: Double Sided Foam Tape

Description:

HEXFIX Mirror Mounting Tape is a cross-linked, flexible polyethylene, double sided, closed cell foam tape. It has low water absorption, good chemical resistance and good UV properties. Coated with a synthetic rubber pressure sensitive adhesive, the foam tape can easily be applied to most common substrates without any mechanical fixings. The material is low irritant, low odour and will not support mould or bacterial growth.

Applications:

Ideally suited for automotive and construction applications including; sealing, gasketing, mounting of nameplates and mirrors (when used in conjunction with a recommended liquid adhesive).

Available Roll Sizes:

24mm x 33m x 1.5mm 24mm x 23m x 3.0mm.

Technical Data:

Product	HEXFIX Mirror Mounting Tape
Colour	White
Adhesive Type	Synthetic rubber resin
Peel Adhesion	25 N/25mm
Elongation Ratio (%)	200
Hardness (Shore C)	15~20
Tensile Strength (kPa)	400 kPa
Tensile Strength (kg/cm ²)	5.6
Tear Strength (kg/cm)	2.4
Compression Strength 25% (kg/cm ²)	0.2
Compression Set @ 50% (%)	23
Compression Deflection (kPa)	10 kPa
Density (kg/m ²)	30 +/- 5
Thermal Conductivity	0.038 W/mK
Water Absorption (g/cm ²)	0.01
Linear Shrinkage (%) (70°C / 22hrs)	5
Operating Temperature Range	-30° to +80° C
Storage & Shelf Life	To obtain best performance, store in a cool dry environment and use product within 12 months from date of manufacture.

Surface Preparation:

All surfaces must be clean, dry, sound and free from dust, oil, rust or any other contamination.

Wipe the joint surfaces using a non-oily solvent such as white spirits on a clean lint-free cloth to remove any oils and contaminants.

Limitations:

This product is not suitable for the following purposes:

Continuous water immersion, non-paintable.

Materials that bleed plasticisers, solvents or release by-products that may inhibit or affect adhesion.

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Mirror installation must be used in conjunction with a suitable liquid adhesive. This product is not designed for long term singular applications. It is formulated to provide aggressive adhesion to mirror backs as part of a system using a liquid adhesive. Lincoln Sentry does not warrant the extended use of this product when used without a supplementary adhesive.

Safety:

Before application of "Mirror Tape 2400", Safety Data Sheets should be read thoroughly.

WARRANTY INFORMATION:

Lincoln Sentry warrants the products to be free of defects in material performance but make no warranty as to appearance. Since methods of application and on-site conditions are beyond our control and can affect performance, we make no other warranty, expressed or implied, including warranties of merchantability and fitness for a particular purpose.