

Bio-Solvent Contact Spray Adhesive



EnviroMight® is a bio-solvent contact spray adhesive that provides high coverage and rapid bonding. Its bio-based formulation features low VOC emissions ensuring that health is never compromised. This contact adhesive is ideally suited for general laminating, whiteboards, and applications in the foam and upholstery industry.

Unrivalled Superpowers

- High Coverage
- Lightning Fast
- Long Open Time
- Flash Grab

- Low VOC
- Fire Tested to AS 1530.3 as per certification sector
- 120°C Heat Resistant

Unleash the Might of EnviroMight

(Directions for Use)

- Working surfaces and adhesive should be between 16°C and 27°C.
- 2. Surfaces to be bonded should be clean and free from oil, dust and other foreign materials.
- 3. Apply adhesive to both surfaces to be bonded.
- 4. Allow adhesive to dry until it is no longer tacky to touch.
- 5. Bring the materials into position and apply as much pressure as possible to obtain optimum bond strength.
- 6. Do not spray below 10°C as condensed moisture may form on the adhesive film and prevent bonding.

Tools Required











Roller

Heroic Applications

- General Purpose Laminating
- General Foam & Upholstery
- Whiteboards

Substrates



HMR Board (Particle Board)



Laminate



Pin Board



MDF



Plywood



ABS Edging



Stainless Steel



Fibreglass



Orthotics

Heroic Attributes

(Typical Properties)

Open time	4 hours		
Flash off time	2-5 Mins		
Coverage	Canister: 33g/m²	Aerosol: 38g/m²	
Viscosity	90cps		
SAFT temp rating	120° C		
Cleaning info	TensorGrip C101		
Total Solids	30%		
System Flammability	Flammable		
Certifications	AS/NZS 1530.3-1999 Fire Test		PASSED

Handling & Storage

- Consult Safety Data Sheet prior to use.
- ✓ Do not store at temperatures over 50°C.
- Avoid exposure to direct sunlight.
- Do not store directly on concrete floor.
- Always store above 15°C
- Always test our adhesives to determine suitability for your particular application prior to use in production

 $Copyright © 2024 by Ouin Global AU \ Ltd \ All \ rights \ reserved. \ This \ publication \ or \ any \ portion \ thereof \ may \ not \ be \ reproduced \ or \ used \ in \ any \ manner \ whatsoever \ without \ the \ express \ written \ permission \ of \ the \ publisher.$

DISCLAIMER OF WARRANTY: The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

Available Sizes



Aerosol

500 mL / 355g



Canister

22 L / 12.7 Kg



Intermediate 108 L / 65 Kg



Colours



Natural



