Briton

1120/1130 SERIES DOOR CONTROLS

The Briton 1120/1130 Series is a non-handed, slimline closer designed to be used on commercial interior/exterior wooden and metal doors e.g. storeroom, office and bathroom doors.

Door closing is hydraulically controlled, with adjustable valve regulators, back check, closing and latching speed, and spring strength power control to give the desired closing speed.

The 1120/1130 Series has a precision rack and pinion mechanism and is easily mounted to the surface of door or the top jamb.

Each standard door closer offers three installation methods including mounting on pull or push sides, top jamb and parallel arm installations.

FEATURES

- Universal, fully reversible, non-handed door closer
- Closer body constructed from pressure die cast aluminium with steel rack and pinion
- Tested to 500,000 cycles
- Factory set to strength 3
- Independent adjustment valves for controlling backcheck, closing and latching speeds
- Fire Resistance tested in accordance with AS1905.1

All door closer options available in Silver, Matt Black and Stainless Steel variants.



Standard / Parallel Arm Door Closer



eel variants

1120B SERIES

Description	Туре	Door Weight	Max. Door Width (Internal)	Power Selection	Carton Qty
1120B Series Regular Arm Adjustable	Regular & Parallel	40-80kg	1100mm	2-4 Adjustable	
1120B Series Track Arm Adjustable	Track	40-60kg	950mm	1-3 Adjustable	6
1120B Series Hold Open Arm	Hold Open	40-80kg	1100mm	2-4 Adjustable	

1130B SERIES

Description	Туре	Door Weight	Max. Door Width (Internal)	Power Selection	Carton Qty
1130B Series Regular Arm Adjustable	Regular & Parallel	40-120kg	1400mm	1-6 Adjustable	
1130B Series Track Arm Adjustable	Track	40-80kg	1100mm	1-4 Adjustable	
1130B Series Hold Open Arm	Hold Open	40-120kg	1400mm	1-6 Adjustable	4
1130B Series Regular Arm Delayed Action	Regular & Parallel	40-120kg	1400mm	1-6 Adjustable	
1130B Series Track Arm Delayed Action	Track	40-80ka	1100mm	1-4 Adjustable	

SPEAK TO YOUR LOCAL BRANCH OR TERRITORY MANAGER TO FIND OUT MORE

National Customer Support Centre

Ph: 1300 551 919

Email: orders@lincolnsentry.com.au

Get Social

@@lincolnsentry

f @lincolnsentry

in Lincoln Sentry Pty. Ltd

